

Material Safety Data Sheet

Updated Feb. 2014

SKM Industries, Inc.

Health 1

Reactivity 0

Flammability 0

Personal Protection B

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Identity: Super Seam Sealer – All Colors	Note: Blank spaces are not
Item No: 01400, 01401, 01450, 01451	permitted. If any item is not
2 oz and 4 oz	applicable, or no information is
Color: Ash Gray, Sand Beige	available, the space must be
	marked to indicate that.
Another Exclusive Product of:	Emergency Telephone Number
SKM Industries, Inc.	800-424-9300 (Chemtrec)
Address (Number, Street, City, State, and ZIP Code)	Telephone Number for
1012 Underwood Road, PO Box 278	Information
	570-383-3062
Olyphant, PA 18447	Date Prepared
USA	February 28, 2014

SECTION 2. COMPOSITION INFORMATION ON INGREDIENTS

Ingredient

Aqueous Adhesive

Pigment

SECTION 3. HAZARDS IDENTIFICATION

Hazardous Ingredients: None Known Threshold Limits: Not established

Effects of Overexposure: No known chronic overexposure effects.

SECTION 4. FIRST AID MEASURES

INGESTION: If swallowed consult a physician.

EYE CONTACT: May cause irritation. In case of eye contact, flush with water for 10-15 minutes. If condition persists, consult a physician.

SKIN CONTACT: Prolonged contact may cause slight irritation of the skin. Wash with soap and water. If irritation develops and persists, get medical attention.

INHALATION: If symptomatic, move to fresh air. Get medical attention if irritation or other symptoms occur.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT: >212 deg F

FLAMMABLE LIMITS: non-flammable

EXTINGUISHING MEDIA: Use water fog, carbon dioxide or chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective

clothing when in confined area.

FLAMMABILITY CLASSIFICATION: OSHA: none DOT: none

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL RESPONSE: Cover with inert absorbent then sweep up and place in waste disposal container. Dispose of in accordance with federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Conditions to avoid: Excessive heat or cold.

Store inside at a temperature of 60-100 degree F. Do not allow product to freeze.

SECTION 8. EXPOSURE CONTROL/PERSONAL PROECTION

EYE PROTECTION: Safety glasses

SKIN PROTECTION: Protective gloves recommended.

RESPIRATORY PROTECTION: None required with adequate ventilation.

VENTILATION: Local ventilation

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None.

WORK/HYGENIC PRACTICES: Wash with soap and water after exposure.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 212 °F

PH: 8.0 typical

WEIGHT PER GALLON: 8.4 lbs typical

SOLUBILITY IN WATER: Not soluble (dispersible)

EVAPORATION RATE: Same as water VAPOR DENSITY: Same as water VOC (grams per liter); Zero calculated APPEARANCE: White/colored paste

ODOR: Mild characteristic

SECTION 10. STABILITY AND REACTIVITY

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizing agents. Avoid heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: None known: Normal Carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

SECTION 12. ECOLOGICAL INFORMATION

No data is currently available.

.

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with federal, state and local regulations.

SECTION 14. TRANSPORT INFORMATION

DOT Hazardous Material Class: Unregulated

This information provided in the Material Safety Data Sheet has been compiled from our experience and data with similar commercially available materials and is believed to be accurate. No guarantee of accuracy is made. It is the user's responsibility to determine the suitability of this information for the adoption of necessary safety precautions and disposal procedures.