



Material Safety Data Sheet

SKM INDUSTRIES, INC, PO Box 278, Olyphant, PA 18447

January 2013

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Identity: Caulk-Aide Bulk - White	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
Item: 06000	
Colors: white	
Formula: SKM121	
Another Exclusive Product of: SKM Industries, Inc.	Emergency Telephone Number: U.S. 800-424-9300 (CHEMTREC) International 703-527-3887
Physical Address: 1012 Underwood Road, Olyphant, PA 18447	Telephone Number for Information: 570-383-3062

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Water - 50%
Titanium Dioxide - 30%
Resin - 10%
Surfacant - 10%

SECTION 3: HAZARDS IDENTIFICATION

Acute hazard: None. KEEP OUT OF REACH OF CHILDREN. Direct contact may cause skin or eye irritation.

SECTION 4: FIRST AID MEASURES

Eyes - Immediately flush eyes with plenty of water for at least fifteen (15) minutes. Get medical attention immediately.
Inhalation: Remove to fresh air. If breathing is irregular seek medical attention. No adverse effects are anticipated from inhalation.
Skin Contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner.
Ingestion: If accidentally swallowed rinse mouth with water and obtain immediate medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: >150°F Method Able Apparatus to British Standard BS 2000
Flammability Limits (% by volume): Non-flammable
Unusual Fire Explosion Hazards: none

SECTION 6: ACCIDENTAL RELEASE MEASURE

In case of spill or accidental release, treat as water based paint.

SECTION 7: HANDLING AND STORAGE

Handling: No special handling requirements.
Storage: KEEP OUT OF REACH OF CHILDREN.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection	None under normal use conditions.
Clothing	None under normal use conditions.
Respirato	None under normal use conditions.
Ventilatio	None under normal use conditions.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

For ink unless otherwise specified.

Boiling Point	>100°C	Specific Gravity (H₂O = 1) @ 70°F	Greater than one (1)
Vapor Pressure (mm-Hg @ 70°F)	No Data	Melting Point	No Data
Vapor Density (AIR = 1)	Greater than one (1)	Evaporation Rate (Butyl Acetate=1)	Less than one (1)
Solubility in Water	100%	PH	No Data

Appearance and Odor - White opaque thick viscosity liquid with paint odor.

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability	Unstable		Conditions to Avoid: Large volume ingestion.
	Stable	X	

Incompatibility (Materials to Avoid): None.

Hazardous Decomposition or By-products: None.

Hazardous Polymerization	May Occur		Conditions to Avoid: No Data
	Will not Occur	X	

SECTION 11: TOXICOLOGICAL INFORMATION

None.

SECTION 12: ECOLOGICAL INFORMATION

Not Available.

SECTION 13: DISPOSAL INFORMATION

Dispose of in accordance with all applicable local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION (Not meant to be all inclusive.)

Non-flammable liquid paint.

SECTION 15: REGULATORY INFORMATION (Not meant to be all inclusive - selected regulations represented)

TSCA INVENTORY: The product on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory.

All ingredients used to manufacture this product are listed on the TSCA Inventory.

SECTION 16: OTHER INFORMATION

SKM has been advised by attorney that the OSHA Hazard Communication Standard does not apply to the SKM products listed in this MSDS. The explanation for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2002 per the code of Federal Regulations. This information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the Hazard Communication Standard covers the product nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard.

These markers and inks contained within conform to ASTM D-4236 and have been examined by certified toxicologist in a program of toxicologic evaluation to assure they are in compliance with the Federal Hazardous Substance Act (FHSA), Labeling of Hazardous Art Materials Act (LHAMA), and ASTM D-4236.
