

SKM MATERIAL SAFETY DATA SHEET

SKM Industries, Inc.
PO Box 278
Olyphant, PA 18447

Updated May 2013
Emergency Medical Number (CHEMTREC): 1-800-424-9300
Creation Date: December 11,2011
Phone: 570-383-3062

-----SECTION I – PRODUCT IDENTIFICATION-----

PRODUCT NAME: WATERBASE CORRECTION FLUID (WHITE)
ITEM #: 1266, 1292, 1294, 45002, 45003
PRODUCT SIZES: 18ml & 22ml
PRODUCT CLASS: CORRECTION FLUID BOTTLE

-----SECTION II – HAZARDOUS INGREDIENTS-----

PIGMENTS: NONE
CATALYST: NONE
VEHICLE: NONE

SOLVENTS: NONE
ADDITIVES: NONE
OTHERS: NONE

-----SECTION III – PHYSICAL DATA-----

BOILING POINT (F') : 215
VAPOR PRESSURE (mm Hg) : N/A
SOLUBILITY IN WATER : DISPERSIBLE
APPEARANCE AND ODOR : OPAQUE WHITE LIQUID, VERY FAINT ODOR
SPECIFIC GRAVITY (H2O=1) : 1.595
EVAPORATION RATE (WATER=1) : 1+
VAPOR DENSITY (AIR=1) : 1+
PERCENT, VOLATILE BY VOLUME (%) : 56

-----SECTION IV – FIRE & EXPLOSION INFORMATION-----

FLASH POINT (METHOD USED): WATERBASED MATERIAL
EXTINGUISHING MEDIA FOR FIRES: CLASS B
FLAMMABLE LIMITS: N/A
UNUSUAL FIRE & EXPLOSION HAZARD: NONE
SPECIAL FIREFIGHTING PROCEDURES: NONE

COMPANY: SKM INDUSTRIES INC.
CORRECTION FLUID (WHITE) - ITEM #1266, #1292 & #45003

PRODUCT: WATERBASE

-----SECTION V – REACTIVITY DATA-----

STABILITY: STABLE
INCOMPATIBILITY : (MATERIALS TO AVOID): STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: NONE
HAZARDOUS POLYMERIZATION PRODUCT: NONE

-----SECTION VI – HEALTH HAZARD DATA-----

THRESHOLD LIMIT VALUE: NONE ESTABLISH
EFFECTS OF OVEREXPOSURE: NONE
EMERGENCY & FIRST AID PROCEDURES: NON-TOXIC MATERIAL. CONTACT WITH EYES, FLUSH WITH WATER FOR 10-15 MINUTES. CONSULT WITH PHYSICIAN.

-----SECTION VII – SPILL OR LEAK PROCEDURES-----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: NONE
WASTE DISPOSAL METHODS: DISPOSE AS NORMAL TRASH.

-----SECTION VIII – SPECIAL PROTECTION INFORMATION-----

RESPIRATORY PROTECTION: NONE
VENTILATION: NONE
EYE PROTECTION: NONE
PROTECTIVE GLOVES: NONE
OTHER PROTECTIVE EQUIPMENT: NONE

-----SECTION IX – SPECIAL PRECAUTIONS-----

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING: STORE IN COOL AREA. KEEP FROM FREEZING NOR EXCEED 120 DEG F.